CSSE 332 -- OPERATING SYSTEMS Rose-Hulman Institute of Technology

Exam 1 Review

Name: _____

Question	Points	Score
Question 1	10	
Question 2	5	
Question 3	5	
Question 4	5	
Question 5	15	
Total:	40	

Question 1. Consider the following snippet of code, take a moment and think carefully about what it is trying to do.

```
for(int i = 0; i < 2; i++) {</pre>
    int pid = fork();
    if(pid == 0) {
3
      int my_pid = getpid();
4
      printf("I am the middle child, my pid is %d!\n", my_pid);
5
      pid = fork();
6
      if(pid == 0) {
        printf("I am the grandchild, my pid is %d\n", my_pid);
8
      } else {
C
        printf("Middle child going away forever!\n");
10
11
         exit(0);
12
      }
13
    }
14
    printf("I am the parent and I just gave birth to my first child!\n");
15 }
```

(a) (5 points) What will print on the screen when this code executes?

(b) (5 points) The code snippet contains crucial bug, what is it and suggest a way to fix it?

Question 2. (5 points) Circle the correct answer each time, suggest a fix if the answer is false.

- On the exam, I should open the man page for fork and wait, lookup functions or macros we haven't used in class and use those to solve the problem (e.g., WNOHANG).
 - A. True
 - B. False
- To wait for a specific child, you can use the wait system call but you pass it an integer pointer (e.g., wait(&status);).
 - A. True
 - B. False
- I would like to execute the binary buffalosay.bin with the input arguments 1 and some integer x. To do so, I would use
 - execlp("./buffalosay.bin", "1", (char*)x, 0);
 - A. True
 - B. False
- There are signals that cannot be overridden or ignored.
 - A. True
 - B. False
- Using alarm(3); guarantees that SIGALRM will be delivered exactly 3 seconds after it has been set.
 - A. True
 - B. False
- You can use the same pipe to communicate in both directions between a parent and a child.
 - A. True
 - B. False
- **Question 3**. (5 points) In the box below, write down the pattern used to wait for a specific child and read its exit status.

Question 4. (5 points) In the box below, write down the general structure of creating a pipe between a parent and a child where the parent is the writer and the child is the reader.

Question 5. (5 points) Consider a scenario with three processes: a parent and two children. The parent has created a pipe between itself and its two children. It then wants to send hello to its first child and bye to its second child. It is crucial that each child receives the message intended for it.

Mohammad suggests to implement this using the following code snippet in each process (assume all pipes and ends are set up correctly).

// parent	// child 1	// child 2
	<pre>char buff[6];</pre>	<pre>char buff[4];</pre>
<pre>// Send "hello" to child 1</pre>		
<pre>write(fd[1], "hello", 5);</pre>	// I want to read the	<pre>// I want to read the</pre>
	hello from my parent	bye from my parent
// Send "bye" to child 2	<pre>read(fd[0], buff, 5);</pre>	<pre>read(fd[0], buff, 3);</pre>
write(fd[1], "bye", 3);	buff[5] = '\0';	buff[4] = '\0';

(a) (5 points) Describe possible ways in which the above code snippet can go wrong!

(b) (5 points) Describe a possible way to fix the above issues.