

Test 3 – Practice Problems for the Paper-and-Pencil portion

Note: These practice problems relate very directly to what you can expect to see on the Paper-and-Pencil portion of Test 3. **Do these problems carefully and check your answers via the online Solution to these problems.**

Many of these problems are similar to problems that you saw on the Paper-and-Pencil portion of Test 2.

Each problem has a *time estimate* that indicates how long the problem might take (at most) for a well-prepared student who had no prior experience in software development before this course. ***If you are taking much longer than the time estimates, work with your instructor*** to learn techniques to solve them more quickly.

A well-prepared student should be able to complete problems 1 through 10 in well under 90 minutes. (The remaining problems are optional.)

Be forewarned that the Paper-and-Pencil portion of Test 3 may not be as generous regarding partial credit as was Test 2. *If you are not 100% clear on ALL parts of ALL of these problems, meet with your instructor*, a course assistant, or another equally qualified person to become solid in your understanding of the concepts that these problems assess:

- Problem 1: Scope of variables, flow of control through function calls and object construction, arguments and parameters.
- Problem 2: Mutation via function calls (when the arguments are mutable), box-and-pointer diagrams, references, mutation versus reassignment.
- Problem 3: Object construction.
- Problem 4: Tracing function calls by hand, returning values, order of operations, ***return*** really ***leaves*** the function.
- Problem 5: Object construction, aliases (two names for the same object).
- Problem 6: Mutation via assignment of the insides of container objects, box-and-pointer diagrams, references, aliases, mutation versus reassignment.
- Problem 7: Mutation via function calls (when the arguments are mutable), box-and-pointer diagrams, references, mutation versus reassignment.
- Problems 8 and 9: Tracing loops within loops by hand.
- Problem 10: Tracing ***while*** loops by hand.

1. [A well-prepared student should not require more than about **7 minutes** to complete this problem.]

Consider the code on the next page. Arrange so that you can see both this page and the next page at the same time. (Un-staple as needed.) On the test, you will receive the code for any problem like this one on a separate page.

The code is a contrived example with poor style but will run without errors. In this problem, you will trace the execution of the code. **As each location is encountered during the run:**

- CIRCLE** each variable that is **defined** at that location.
- WRITE** the **VALUE** of each variable that you **circled** directly **BELOW** the circle.

For example, the run starts in **main**, as usual. The first of the seven locations to be **encountered** is **Location 6**. At Location 6, the only variables defined are **a** and **z**, with values **5** and **3** at that point of the program's run. So, on the row for Location 6, I have circled **a** and **z** and written their values at Location 6 directly below them.

Note that you fill out the table in the order that the locations are encountered, **NOT from top to bottom**. **ASK FOR HELP IF YOU DO NOT UNDERSTAND WHAT THIS PROBLEM ASKS YOU TO DO.**

Location 1 the 1 st time that it is encountered	a	w	z	self.w	cat.w	dog.w	cat.a
Location 1 the 2 nd time that it is encountered	a	w	z	self.w	cat.w	dog.w	cat.a
Location 2 the 1 st time that it is encountered	a	w	z	self.w	cat.w	dog.w	cat.a
Location 2 the 2 nd time that it is encountered	a	w	z	self.w	cat.w	dog.w	cat.a
Location 3	a	w	z	self.w	cat.w	dog.w	cat.a
Location 4	a	w	z	self.w	cat.w	dog.w	cat.a
Location 5	a	w	z	self.w	cat.w	dog.w	cat.a
Location 6	a	w	z	self.w	cat.w	dog.w	cat.a
	5		3				
Location 7	a	w	z	self.w	cat.w	dog.w	cat.a

Code for Problem 1:

Arrange so that you can see this code and the problem itself at the same time. (Un-staple as needed.)

The arrows are there to help you see where the seven Locations are in the code.

```
class Animal(object):
    def __init__(self, w):
        a = 10
        ##### Location 1 ←

        self.w = a * w    # MULTIPLY, not add
        ##### Location 2 ←

def make_animals(z, a, w):
    ##### Location 3 ←

    dog = Animal(w + a)
    ##### Location 4 ←

    cat = Animal(w + z)
    ##### Location 5 ←
    return cat.w

def main():
    a = 5
    z = 3
    ##### Location 6 ←

    a = make_animals(a, z, z + 1)
    ##### Location 7 ←

main()
```

2. [A well-prepared student should not require more than about **15 minutes** to complete this problem.]

Consider the code on the next page. Arrange so that you can see both this page and the next page at the same time. (Un-staple as needed.) On the test, you will receive the code for any problem like this one on a separate page.

The code is a contrived example with poor style but will run without errors. Trace the code's execution and **draw a box-and-pointer diagram on a separate sheet of paper** as you trace the code's execution.

As you draw the box-and-pointer diagram, write (in the box below) what gets printed when *main* runs. Write Point objects as in this example: **(100, 150)**.

Output:

Beta 1:

Beta 2:

Beta 3:

Beta 4:

Main 1:

Main 2:

Main 3:

Main 4:

Main 5:

Reminder:

You must **draw** (on a separate page) a

**** box-and-pointer ****

diagram for this problem.

Code for Problem 2:

Arrange so that you can see this code and the problem itself at the same time. (Un-staple as needed.)

```
def main():
    radius = 70
    center = Point(100, 150)
    p = center
    seq = [radius, center.x, p, 10]

    ans = beta(radius, center.x, p, seq)

    print('Main 1:', radius)
    print('Main 2:', center)
    print('Main 3:', p)
    print('Main 4:', seq)
    print('Main 5:', ans)

def beta(radius, x, p, seq):
    radius = 33
    p.x = 678
    seq[0] = 444
    seq[3] = 222
    seq = [100, 200, 300]
    p = Point(600, 700)
    p.y = 99

    print('Beta 1:', radius)
    print('Beta 2:', x)
    print('Beta 3:', p)
    print('Beta 4:', seq)
    return seq[2]

main()
```

3. [A well-prepared student should not require more than about **1 minute** to complete this problem.]

When the code in the previous problem runs: (circle your choice for each of the following)

- a. How many *Point* objects are constructed in *main*? 0 1 2 3 4
- b. How many *Point* objects are constructed in *beta*? 0 1 2 3 4

4. [A well-prepared student should not require more than about **7 minutes** to complete this problem.]

Consider the code snippet below. It is a contrived example with poor style, but it will run without errors. What does it print when it runs?

Write your answer in the box to the right of the code.

```
def main():
    print('Main:', three())

def three():
    print('Three 1:', one(7))
    return two(10) + (100 * one(5))
    print('Three 2:')

def two(y):
    answer = one(2 * y)
    print('Two:', y, answer)
    return (5 + answer)

def one(x):
    print('One:', x)
    return (3 * x)

main()
```

Output:

5. [A well-prepared student should not require more than about **1 minute** to complete this problem.]

Consider the following four statements:

```
p1 = rg.Point(4, 5)
p2 = rg.Point(p1.x, p1.y)
p3 = p1
p4 = p2
```

At this point, how many **rg.Point** objects have been constructed? **1** **2** **3** **4**
(circle your choice)

6. [A well-prepared student should not require more than about **7 minutes** to complete this problem.]

Consider the code snippet to the right. Trace the execution of the code snippet and **draw a box-and-pointer diagram on a separate sheet of paper** as you trace the code's execution.

After the code snippet is executed, what are the values of the variables? (Write your answer in the spaces provided below.)

p1.x = _____

p1.y = _____

p2.x = _____

p2.y = _____

p3.x = _____

p3.y = _____

p4.x = _____

p4.y = _____

```
p1 = rg.Point(4, 5)
p2 = rg.Point(p1.x, p1.y)
p3 = p1
p4 = p2

p3.x = 99
p4.y = 600
p4 = rg.Point(42, 42)
```

Reminder:

You must *draw* (on a separate page) a

**** *box-and-pointer* ****

diagram for this problem.

7. [A well-prepared student should not require more than about **12 minutes** to complete this problem.]

Recall that our Point class has instance variables **x** and **y** for its x and y coordinates.

Consider the code snippets below. They are contrived examples with poor style but will run without errors. For each code snippet:

1. Trace the code snippet's execution when **main** runs and **draw a box-and-pointer diagram on a separate sheet of paper** as you trace the code snippet's execution.
2. Write below what the code snippet prints.

(Each code snippet is an independent problem.)

```
def main():
    p1 = Point(11, 12)
    p2 = Point(77, 88)
    p3 = foo(p1, p2)
    print(p1.x, p1.y)
    print(p2.x, p2.y)
    print(p3.x, p3.y)

def foo(p1, p2):
    p1 = Point(0, 0)
    p1.x = 100
    p2.y = 200
    p3 = Point(p2.x, p1.y)
    return p3
```



Prints: _____


```
def main():
    a = [1, 2, 3]
    b = [100, 200, 300]
    c = foofoo(a, b)
    print(a)
    print(b)
    print(c)

def foofoo(a, b):
    a = [11, 22, 33]
    a[0] = 777
    b[0] = 888
    x = [a[1], b[1]]
    return x
```



Prints: _____

Reminder: You must *draw* (on a separate page) *TWO* ** box-and-pointer diagrams **** for this problem.**

8. [A well-prepared student should not require more than about **10 minutes** to complete this and the next problem, combined.]

Consider the code snippet below. It is a contrived example with poor style, but it will run without errors. What does it print when *main* runs?

Write your answer in the box to the right.

```
def main():  
    for j in range(5):  
        for k in range(j):  
            print(j, k)
```


Output:

Output:

9. Consider the code snippet below. It is a contrived example with poor style, but it will run without errors. What does it print when *main* runs?

Write your answer in the box to the left.

```
def main():  
    for j in range(5):  
        print('here')  
        for k in range(1, j - 1):  
            print(j, k)  
  
        print('there')  
        for k in range(2, j + 1):  
            print(j, k)
```



10. [A well-prepared student should not require more than about **5 minutes** to complete this and the next problem, combined.]

Consider the code snippet below. It is a contrived example with poor style, but it will run without errors. What does it print when it runs?

Write your answer in the box to the right.

Note: The expression:

```
while BLAH:
```

```
...
```

makes the body of the *while* expression keep running “while” BLAH is true. For example:

```
while x > 20:
```

```
...
```

makes the body (that is, indented part) of the *while* expression keep running while *x* is greater than 20. (And presumably *x* is decreasing inside the body of the loop, so eventually *x* is less than or equal to 20 and the loop then exits.)

```
x = 2
while x < 9:
    print(x)
    x = x + 3
print('One', x)
```

```
y = 2
while True:
    print(y)
    if y > 9:
        break
    y = y + 3

print('Two', y)
```

Output:

The remaining problems are **OPTIONAL**. Do them if you want to reinforce further the concepts of *references, box-and-pointer diagrams, mutation, nested loops for sequences and printing*.

11. True or false: **Variables are REFERENCES to objects.** **True** **False** (circle your choice)

12. True or false: **Assignment** (e.g. **`x = 100`**)
causes a variable to refer to an object. **True** **False** (circle your choice)

13. True or false: **Function calls** (e.g. **`foo(54, x)`**)
also cause variables to refer to objects. **True** **False** (circle your choice)

14. Give one example of an object that is a **container** object:

15. Give one example of an object that is **NOT** a **container** object:

16. True or false: When an object is mutated, it no longer refers
to the same object to which it referred prior to the mutating.
(circle your choice) **True** **False**

17. Consider the following statements:

```
c1 = rg.Circle(rg.Point(200, 200), 25)
c2 = c1
```

At this point, how many ***rg.Circle*** objects have been constructed? **1** **2**
(circle your choice)

18. Continuing the previous problem, consider an additional statement that follows the preceding two statements:

```
c1.radius = 77
```

True or False: After the above statement executes, the variable ***c1***
refers to the same object to which it referred prior to this statement. **True** **False**
(circle your choice)

19. Continuing the previous problems:

- What is the value of ***c1***'s radius after the
statement in the previous problem executes? **25** **77** (circle your choice)
- What is the value of ***c2***'s radius after the
statement in the previous problem executes? **25** **77** (circle your choice)

20. In Session 9, you implemented a **Point** class. Recall that a **Point** object has instance variables **x** and **y** for its x and y coordinates.

Consider the code in the box below. On the **next** page, draw the **box-and-pointer diagram** for what happens when **main** runs. Also on the next page, show what the code would **print** when **main** runs.

```
def main():
    point1 = Point(8, 10)
    point2 = Point(20, 30)
    x = 405
    y = 33

    print('Before:', point1, point2, x, y)

    z = change(point1, point2, x, y)

    print('After:', point1, point2, x, y, z)

def change(point1, point2, x, a):
    print('Within 1:', point1, point2, x, a)
    point2.x = point1.x
    point2 = Point(5, 6)
    point1.y = point2.y
    x = 99
    point1.x = x
    a = 77

    print('Within 2:', point1, point2, x, a)

    return a
```

Draw your box-and-pointer diagram here:

What prints when *main* runs?

Assume that *Point* objects get printed as per this example: **Point(8, 10)**.

Before: _____

Within 1: _____

Within 2: _____

After: _____

21. Consider the code snippet in the box below. It is a contrived example with poor style, but it will run without errors. What does it print when **main** runs?

Write your answer in the box shown to the right of the code.

```
def main():
    seq = [('one', 'two', 'three', 'four'),
           ('five', 'six', 'seven'),
           ('eight', 'nine', 'ten'),
           ['is this ok?'],
           (),
           ('123456', '1234')]

    for k in range(len(seq)):
        for j in range(len(seq[k])):
            print(j, k)
            if len(seq[k][j]) > 3:
                print(seq[k][j],
                      len(seq[k][j]))
```

Output:

22. In the space below, write an implementation for the function whose specification is shown in the following box. Do NOT use your computer for this (or for any other of these paper-and-pencil problems).

```
def shape(r):  
    """  
    Prints shapes per the following examples:  
    When r = 5:                                When r = 3  
        *****5                                ***3  
        ****54                                  **32  
        ***543                                  *321  
        **5432  
        *54321  
    Precondition: r is a non-negative integer.  
    For purposes of "lining up", assume r is a single digit.  
    """
```