


## Chapter 21

### A Priority Queue: The Binary Heap



Addison-Wesley  
is an imprint of




Copyright © 2010 Pearson Education, publishing as Addison-Wesley. All rights reserved

```
1  /**
2  * Establish heap order property from an arbitrary
3  * arrangement of items. Runs in linear time.
4  */
5  private void buildHeap( )
6  {
7      for( int i = currentSize / 2; i > 0; i-- )
8          percolateDown( i );
9  }
```

**figure 21.16**


Implementation of the  
linear-time `buildHeap`  
method



**figure 21.17**  
 (a) Initial heap;  
 (b) after  
 percolateDown(7)


**figure 21.18**

(a) After  
 percolateDown(6);  
 (b) after  
 percolateDown(5)




**figure 21.19**

(a) After  
percolateDown(4);  
(b) after  
percolateDown(3)




**figure 21.20**

(a) After  
percolateDown(2);  
(b) after  
percolateDown(1)  
and buildHeap  
terminates




**figure 21.25**  
Max heap after the  
buildHeap phase



Copyright © 2010 Pearson Education, publishing as Addison-Wesley. All rights reserved


1-7



**figure 21.26**  
Heap after the first  
deleteMax operation

Copyright © 2010 Pearson Education, publishing as Addison-Wesley. All rights reserved

1-8



**figure 21.27**  
Heap after the second deleteMax operation